

Script meetings/bin/meeting-follow

```
./bin/meeting-follow
```

Display the transcript while it is generated.

Usage

```
meeting-follow
```

Script

```
#!/usr/bin/env bash
set -euo pipefail

BASE="$HOME/meetings/recordings"
CURRENT="$BASE/.current"

echo "⏳Waiting for active meeting session..."

# Wait until a current session is announced
while [[ ! -f "$CURRENT" ]]; do
    sleep 0.5
done

SESSION="$(cat "$CURRENT")"
META="$SESSION/meta.env"
TRANSCRIPT="$SESSION/transcript.txt"

# Check if live transcription is disabled for this session
if [[ -f "$META" ]]; then
    # shellcheck disable=SC1090
    source "$META"
```

```
fi

if [[ "${NO_TRANSCRIPT:-0}" -eq 1 ]]; then
    echo "⚠ This session was started with --no-transcript."
    echo "  No live transcript available."
    exit 1
fi

echo "  Following transcript:"
echo "    Session: $SESSION"
echo "    File:    $TRANSCRIPT"
echo "----"

# Wait until transcript file exists
while [[ ! -f "$TRANSCRIPT" ]]; do
    sleep 0.5
done

tail -f "$TRANSCRIPT"
```

Expected behaviour:

`meeting-follow` will check the file `$HOME/meetings/recordings/.current` if an active transcript session exists. If not, it waits until the information about the active session has been added by `meeting-start` and will then start displaying the transcript.